


DENON

Hi-Fi Component / Amplifier

SERVICE MANUAL

MODEL PMA-232

**SOLID STATE STEREO
INTEGRATED AMPLIFIER**



NIPPON COLUMBIA CO., LTD.

TABLE OF CONTENTS

SPECIFICATIONS	1	ETC-104 MUTING CONTROL UNIT PARTS LIST	7
DISASSEMBLY INSTRUCTIONS	2	CHASSIS & CABINET GROUP PARTS LIST	7
PRINTED CIRCUIT BOARD PATTERNS AND PARTS LIST		ADJUSTMENTS AND MEASUREMENT PROCEDURES	8
ETC-99B EQUALIZER, TONE AMP UNIT	3	WIRING DIAGRAM	9
ETC-85D POWER AMP PROTECTOR & POWER SOURCE UNIT	5		

SPECIFICATIONS

Type: All silicon transistor stereo pre-main amplifier

POWER AMPLIFIER & PRE AMPLIFIER SECTION

Circuit system: Pure complementary, Whole-stage-direct-

connection, 7 power source OCL circuit

Rated output power: 45W/45W (load, 8 ohms) at T.H.D. 0.1%

(Each channel driven): 62 W/62W (load, 4 ohms) at T.H.D. 0.1%

Rated output power: 38W + 28W (load, 8 ohms) at T.H.D. 0.1%

(Both channel driven): 47W + 47W (load, 4 ohms) at T.H.D. 0.1%

Harmonic distortion: Lower than T.H.D. 0.1% (at 8 Watts and 20Hz to 20KHz)

Cross modulation

distortion: Lower than 0.1% (at equivalent sign wave rated output)

Power bandwidth: 20Hz — 30KHz (at T.H.D. 0.3%)

Input sensitivity/input

impedance: (at 1KHz) PHONO: 2.2mV r.m.s. 50K ohms $\pm 10\%$

TUNER: 14.0mV r.m.s. 80K ohms $\pm 10\%$

AUX: 14.0mV r.m.s. 80K ohms $\pm 10\%$

Maximum allowable: PHONO: More than 200mVr.m.s. (1KHz)

Input level:

Equalizing characteristic,

RIAA deviation: $\pm 0.4\text{dB}$ (at 20Hz — 20KHz, Rec out)

TONE CONTROL SECTION

Transmission: 20Hz — 50KHz $\pm 1\text{ dB}$ at TONE CENTER position

Tone control: BASS: +7.5dB, —5.0dB at 100Hz
TREBLE: +7.5dB, —5.0dB at 10KHz

Low filter cutoff

frequency: 15Hz (—12.3dB)

Power requirement: AC 220/240V changeable, 50Hz, 120V 60Hz (For USA, Canada)

Power consumption: 250W


Dimensions: 396mm (W) x 147mm (H) x 281mm (D)

Weight: 9 Kg

DISASSEMBLY INSTRUCTIONS


REF. NO.	NO.	PARTS	REF. NO.	NO.	PARTS
(1)	1020032109	TOP COVER	(16)	2048014108	6P WRAPPING PIN JACK
(2)	4110105105	MAIN CHASSIS	(17)	2048015107	4P WRAPPING PIN JACK
(3)	1040016008	FOOT	(18)	EP-71141	PUSH TERMINAL
(4)	1440165300	FRONT PANEL	(19)	2050043109	GND TERMINAL
(5)	1120091202	KNOB			
(6)	1120090106	KNOB			
(7)	1130065105	KNOB			
(8)	1160004107	KNOB SHEET			
(9)	4110077301	FRONT CHASSIS			
(10)	4310040400	SLIDER			
(11)	4430069015	COLLOR			
(12)	4140069004	SHIELD PLATE			
(13)	2062002002	AC CORD WITH PLUG			
(14)	2020012005	FUSE HOLDER			
(15)	2061015058	FUSE 1.6A (TIME LAG)			

PARTS LOCATION



Ref. No.	Part No.	Part Name	Description		
R29,30	2410372009	RD14B2E274J	1/4W 270Kohm	±5%	Carbon Film Resistor
R31,32,33,34	2410345007	RD14B2E203J	1/4W 20Kohm	±5%	"
R37,93,94	2410338001	RD14B2E103J	1/4W 10Kohm	±5%	"
R38	241029000	RD14B2E101J	1/4W 100 Ohm	±5%	"
R39,40	2420193016	RC05GF2E155KF	1/2W 1.5Mohm	±10%	"
R43,44,47,48	2410365003	RD14B2E134J	1/4W 130Kohm	±5%	"
R51,63,64	2410378003	RD14B2E474J	1/4W 470Kohm	±5%	"
105,106					
R52	2410352003	RD14B2E393J	1/4W 39Kohm	±5%	"
R53,54	2410341001	RD14B2E133J	1/4W 13Kohm	±5%	"
R55,56	2410302008	RD14B2E331J	1/4W 330 Ohm	±5%	"
R61,62	2410312001	RD14B2E821J	1/4W 820 Ohm	±5%	"
R65,66,67,	2410342000	RD14B2E153J	1/4W 15Kohm	±5%	"
68,109,110					
R69,70	2410335004	RD14B2E752J	1/4W 7.5Kohm	±5%	"
R73,74,75,76	2420203016	RC05GF2E106KF	1/2W 10Mohm	±10%	Carbon Composite Resistor
R77,78	2410360008	RD14B2E823J	1/4W 82Kohm	±5%	Carbon Film Resistor
R79,80,87,88	2410339000	RD14B2E113J	1/4W 11Kohm	±5%	"
R81,82,85,86	2410343009	RD14B2E163J	1/4W 16Kohm	±5%	"
R84,83,132	2410354001	RD14B2E473J	1/4W 47Kohm	±5%	"
R89,91,92,97,98	2410330009	RD14B2E472J	1/4W 4.7Kohm	±5%	"
R95,96	2410331008	RD14B2E512J	1/4W 5.1Kohm	±5%	"
R99,100	2410253018	RD14B2H684JF	1/2W 680Kohm	±5%	"
R103,104	2410334005	RD14B2E682J	1/4W 6.8Kohm	±5%	"
R107	2440033017	RS14B3A221JNBF	1W 220 Ohm	±5%	Metal Oxide Resistor
R121,122	2420195014	RC05GF2E225KF	1/4W 2.2Mohm	±10%	Carbon Composite Resistor
R125,126	2410374007	RD14B2E334J	1/4W 330Kohm	±5%	Carbon Film Resistor
R127,128	2410336003	RD14B2E822J	1/4W 8.2Kohm	±5%	"
R131	2410346006	RD14B2E223J	1/4W 22Kohm	±5%	"
TR1,2,3,4	2730158013	2SC1775(F)	Transistor		
7,8,11,12					
TR5,6	2730161000	2SC1212AWT(B)	"		
TR9,10	2710071000	2SA743A(B)	"		
TR21,22	2730158013	2SC1775(F)	"		
S1	2120062007	Function Switch			
S2	2120064005	Treble Switch			
S3	2120063006	Base Switch			
VR2	2110092003	V2422P25RZ254K	For Balance Volume		
	EP-56671H	Terminal			
	2220235006	Printed Circuit Board			

ETC-85D POWER AMP PROTECTOR & POWER SOURCE UNIT



ETC-85D POWER AMP PROTECTOR & POWER SOURCE UNIT PARTS LIST

Ref. No.	Part No.	Part Number	Description			
C1,2	2544044012	CE04W1H010=F	1uF	50V	Electrolytic Capacitor	
C3,4	2533623017	CC45SL1H680JF	68PF	±5%	50V	Ceramic Capacitor
C5,6	2544003011	CE04W0J101=F	100uF		63V	Electrolytic Capacitor
C7,8	NON					
C9,10	2533621019	CC45SL1H560JF	560PF	±5%	50V	Ceramic Capacitor
C11,12	2544051018	CE04W1H221=F	220uF		50V	Electrolytic Capacitor
C13,14	2544039001	CE04W1V221=	220uF		35V	"
C15,16	2533595019	CC45SL1H020CF	2PF	±5.25PF	50V	Ceramic Capacitor
C17,18,23	2544046010	CE04W1H4R7=F	4.7uF		50V	Electrolytic Capacitor
C19,20	2551130045	CQ93M1H104JF	0.1uF	±5%	50V	Plastic Film Capacitor
C21,22	2531026014	CK45F1H473ZF	0.047uF		50V	Ceramic Capacitor
C51,52	NON					
C53,55	2531021019	CK45F1H102ZF	0.001uF		50V	"
C54	2549005030	CE04=1E100MHS	10uF		25V	Electrolytic Capacitor
C56	2531050019	CK45E2H102PF	0.001uF		500V	Ceramic Capacitor
C57,58	2544006018	CE04W0J471=F	470uF		7.3V	Electrolytic Capacitor
C81	2531053016	CK45E2H103PF	0.01uF		500V	Ceramic Capacitor
C82	2544063019	CE04W1K221=	220uF		80V	Electrolytic Capacitor
C83	2531002012	CK45B1H471KF	470PF		50V	Ceramic Capacitor
C84	2544063006	CE04W1K101=	100uF		80V	Electrolytic Capacitor
C85	2544053003	CE04W1H471=	470uF		50V	"
C86	2544026001	CE04W1E330=	33uF		50V	"
R1,2,19,20	2410314012	RD14B2E102JF	1/4W 1Kohm	±5%		Carbon Film Resistor
R3,4	2410360011	RD14B2E823JF	1/4W 82Kohm	±5%		"
R5,6	2410347018	RD14B2E243JF	1/4W 24Kohm	±5%		"
R7,8	2410320019	RD14B2E182JF	1/4W 1.8Kohm	±5%		"
R9,10	2410336016	RD14B2E822JF	1/4W 8.2Kohm	±5%		"
R11,12	2410317019	RD14B2E132JF	1/4W 1.3Kohm	±5%		"
R13,14	NON					
R15,16,83	2410346019	RD14B2E223JF	1/4W 22Kohm	±5%		"
R17,18,25	2410290013	RD14B2E101JF	1/4W 100 Ohm	±5%		"
26,27,28						
R21,22	2442001021	RS14B3A242JNBF	1W 2.4Kohm	±5%		Metal Oxide Film Resistor
R23,24	2440096012	RS14B3D681JNBF	2W 680 Ohm	±5%		"
R29,30,31	2430023008	RW99=3FR47J	3.15W 0.47 Ohm	±5%		Wire wound Resistor
32						
R33,34	2440129015	RS14B3F100JNBF	3.15W 10 Ohm	±5%		Metal Oxide Film Resistor
R51~58	NON					
R59	2410342013	RD14B2E153JF	1/4W 15Kohm	±5%		Carbon Film Resistor
R60,69,71,72	2410338014	RD14B2E103JF	1/4W 10Kohm	±5%		"

Ref. No.	Part No.	Part Name	Description
R61	NON	RD14B2E473JF	1/4W 47Kohm ±5% Carbon Film Resistor
R62	2410354014	RD14B2E270JF	1/4W 27 Ohms ±5% "
R63	2410276011	RD14B2H824JF	1/2W 820Kohm ±5% "
R64	2410255016	RD14B2E294JF	1/4W 390Kohm ±5% "
R65	2410376018		
R66	NON	RD14B2H105JF	1/2W 1Mohm ±5% "
R67	2410257014	RD14B2E562JF	1/4W 5.6KOhm ±5% "
R68	2410332010	RS14B3A271JNBF	1W 270 Ohm ±5% Metal Oxide Film Resistor
R70	2440034016	RD14B2E472JF	1/4W 4.7Kohm ±5% Carbon Film Resistor
R73	2410330012	RS14B3D221JNBF	2W 220 Ohm ±5% Metal Oxide Film Resistor
R74,75	2440090018	Fuseable Resistor	2.2 Ohm
R81	EP-6975	RS14B3D102JNBF	2W 1Kohm ±5% Metal Oxide Film Resistor
R82	2440098010	RD14B2E221JF	1/4W 220 Ohm ±5% Carbon Film Resistor
R84	2410298015	RD14B2E474JF	1/4W 470Kohm ±5% Carbon Film Resistor
R85	2410378016	RS14B3D511JNB	2W 510 Ohm ±5% Metal Oxide Film Resistor
R86	2442003029	RD14B2E103J	1/4W 10Kohm ±5% Carbon Film Resistor
R90	2410338001	Solid Volume	4.7Kohm
VR1,2	EP-546211H	"	470 Ohm
VR3,4	EP-54625H	"	Variable Resistor
TR1,2,3,4	2730158026	2SC1775 (E)	Transistor
TR5,6	2710072009	2SA850(D)	"
TR7,8,54,81	2730161000	2SC1212AWT(B)	"
TR9,10	2710071000	2SA743A(B)	"
TR11,12	2740040001	2SD581(B)	Transistor (Out Put Power)
TR13,14	2720027002	2SB611(B)	Transistor (Out Put Power)
TR51,52	NON		
TR53	2710040057	2SA673A (C)	Transistor
TR56,82	2730158013	2SC1775(F)	"
TR57	2730116039	2SC1345(D)	"
TR58	2730162009	2SC1775A(F)	"
D1,2	2760155028	VD1122	Varistor
D3,4	2760132025	STV-3H(O)	Diode
D5,6	2760156027	VD1222	Varistor
E55,56,57,58	2760001004	1N34A	Diode
D85,86	2760057016	V06C	Diode
D87	2760067006	AW01-15	Zenner Diode
F81,82	EP-71329	Fuse 4A (Time Lug)	For "+B" "-B" Fuse
	EP-5870	Fuse Holder	
	4170045001	Radiator	For TR11,12,13, and 14
		Insulating Sheet	For TR11,12,13, and 14
	EP-6071	Base Pin	
	2034025004	3P Connector (B) plug	
	2036026001	4P Connector (B) Plug	
	4150065001	Holder	For P.C. Board Holder
	2220204202	Printed Circuit Board	

ETC-104 MUTING CONTROL PARTS LIST

Ref. No.	Part No.	Part Name	Description
C1,2	2551114003	CQ93M2D473M	0.047 uF 200V ±50%
R1,2	2410360008	RD14B2E823J	1/4W 82Kohm ±5% Carbon Film Resistor
R3	2410365003	RD14B2E134J	1/4W 130Kohm ±5% "
D1,2,3,4	2760057016	V06C	Diode
	EP-5667H	Terminal	
	2220282004	Printed Circuit Board	

GE-4003-1 CHASSIS & CABINET GROUP

Ref. No.	Part No.	Parts Name	Remarks
C1,2,3	2518001007	CP05C=AC103MC	0.01uF ±20% 450VAC Oil Capacitor
	2546011001	CF64W1H682=	68000uF 50V Electrolytic Capacitor
	2124047002	Slide Switch	For Power on off Switch
	2120060009	Speaker Switch	For Voltage Selector Switch
	2124048001	Slide Switch	For Speaker Switch
			For Tape Monitor Switch
			For Filter Switch
	2048008004	Head Phone Jack	
	3930017034	Lamp Ass'y	For Pilot Lamp (6.3V, 0.15A)
	2110118000	V2420N30KR254	For Main Volume
	EP-71141	Push Terminal	For Speaker Connecting Terminal
	2048015107	4P Wrapping Pin Jack	For Tape Jack
	2048014108	6P Wrapping Pin Jack	For Phono, Aux, Tuner Input Jack
	2090012006	Short Pin	For Tape PB Short Pin
	2850047008	Earth Terminal	For Gnd. Terminal
	2020012005	Fuse Holder	For AC Line Fuse Holder
	2061015058	Fuse 1.6A (Time Lag)	For AC Line Fuse
	2062002002	AC Cord with Plug	For Europe
	2062009005	AC Cord with Plug	For Australia
	2034059038	3P Connector Cord	For Connection Cord From ETC-85 To Head Phono
	2034069028	3P Connector Cord	For Connection Cord
	2030079009	1P Connector Ass'y	For Connection Cord From SP SW To ETC-85
	2030076028	1P Connector (A) Ass'y	For Connection Cord From Earth to ETC-85
	2030072035	1P Connector (A) Ass'y	For Connection Cord From SP SW To ETC-85
	2030070079	1P Connector Ass'y	For Connection Cord From Earth To ETC-85
	2335023103	Power Trans Ass'y	
	1440165106	Front Panel Ass'y	
	1120091202	Knob	For Main Volume
	1120091016	Knob	For Function, Balance, Bass, Treble and Speaker
	1130065105	Knob	For Power, Low Filter and Monitor Switch
	1160004000	Knob Sheet	
	1020032002	Top Cover	
	4110104203	Main Chassis Ass'y	

ADJUSTMENTS AND MEASUREMENTS PROCEDURES

INSTRUCTIONS FOR ADJUSTING MIDPOINT ELECTRIC POTENTIAL AND IDLING ELECTRIC CURRENT OF POWER AMPLIFIER UNIT.

To ensure accurate adjustment of the midpoint electric potential and idling electric current of the PMA-232 Power Amplifier Unit (ETC-85), and adjustment should be performed in the manner indicated below:

1. MEASURING INSTRUMENTS

A. DC Voltmeter (200mV)

B. DC Ammeter (100mA)

Note: One each of the above mentioned instruments will suffice if a test is conducted on only one channel at a time.

2. CONNECTION

A. Connect one DC voltmeter to the left and one to the right channel of the SPEAKER terminals. (See Fig. 18)

B. Remove the plug (red wire) from the No. 1 terminal (+B) of the Power Amplifier Unit (ETC-85) and connect the DC ammeter to each channel. (See Fig. 19)

3. PROCEDURES

- Set the power supply at pre-set voltages of the PMA-232 (AC 220/240V:50Hz, 120V (FOR USA, CANADA))
- Wait three minutes after Power switch is ON.

C. For adjusting midpoint voltage, turn the VR-1 (4.7 Kohm) so that voltage reading on the DC voltmeter (V) becomes 0 (zero): $V=0$. The condition is abnormal if the value exceeds 100 mV.

D. Following adjustment of the midpoint voltage potential, adjust the idling electric current to 45 mA on the DC ammeter by rotating the VR-2 (470 ohm). $I=45\text{mA}$.

Lock it with paint after adjustment is completed.




Fig. 1





Fig. 2

DENON MODEL PMA-232 WIRING DIAGRAM



NOTES:

- ALL RESISTANCE VALUES IN OHM(S), K = 1,000 OHMS, M = 1,000,000 OHMS.
- ALL CAPACITANCE VALUES IN MICRO FARAD(S), P = MICRO-MICRO FARADS.
- EVERY VOLTAGES AND CURRENTS IS MEASURED AT NO SIGNAL INPUT CONDITION.

S1a-b : FUNCTION SW (1-AUX, 2-PHONO, 3-TUNER)
 S2a-b : TREBLE SW (1--5dB, 2--2.5dB, 3-0dB, 4--2.5dB, 5--5dB, 6--7.5dB)
 S3a-b : BASS SW (1--5dB, 2--2.5dB, 3-0dB, 4--2.5dB, 5--5dB, 6--7.5dB)

S10a-b : POWER SW (1-ON, 2-OFF)
 S11a-b : TAPE MONITOR SW (1-TAPE, 2-SOURCE)
 S12a-b : SPEAKER SW (1 OFF, 2-A, 3-B, 4-B)
 S13a-b : LOW CUT FILTER (1-ON, 2-OFF)